

PRODUCT CATALOG



2025

أرضيات SPC



SPC

منتج بجودة عالية



WMS-601

Size:182*1220*5mm



WMS-602

Size:182*1220*5mm



SPC

منتج بجودة عالية



WMS-603

Size:182*1220*5mm



WMS-604

Size:182*1220*5mm



SPC

منتج بجودة عالية



WMS-605

Size:182*1220*5mm



WMS-606

Size:182*1220*5mm



SPC

منتج بجودة عالية



WMS-607

Size:182*1220*5mm



WMS-608

Size:182*1220*5mm

هرمي

Herringbone





SPC



WMS-901

Size: 128*640*5mm



WMS-902

Size: 128*640*5mm



WMS-903

Size: 128*640*5mm



SPC

Technical Data .SPC 5.0

| Characteristics | Delection method | Detection result |
|--|------------------|--|
| Dimension | EN 427 | 640mm*128mm 610mm*305mm |
| Thickness in total | EN 428 | 5mm |
| Thickness ofwear layers | EN 429 | 0.3mm |
| Weight in total | EN 430 | 17KG 19KG |
| Peeling Strenght of layers | EN 431 | ≥75N/50mm |
| Shearing force of layers | EN 432 | good |
| Residual Indentation after static load | EN 433 | ≤ -0.04 mm |
| Dimension Stability | EN 434 | shrinkage≤ ±0.08% warping≤±4mm |
| Flexibility-10mm mandrel | GB7657 | MOR ≥18Mpa MOE≥3500Mpa |
| Resistance to chemicals | EN 423 | Resistant |
| Bearing a castor chair | EN 425 | After 25000 cycles,test specimens no visible damage |
| Color fastness to light | ISO 105 B02 | 6 |
| Wear resistance | EN660 | 500 grams of pressure The amount of Wear<0.015g/1000r |
| Toxic | EN71-3 | Complies |
| GB/T4085 PVC block material performance testing GB 8624 B1 gradc flammability testing | | EN14041 0200130 DOP 306 |
| Slip resistance | | R9 |
| Performance classification | | 23,34,43 |
| CNS 8907 anti-flaming tesing | | Pass |
| Resistance to fire | | VFPA CLASS B |

SPC FLOOR ADVANTAGE



Non- Formaldehyde



Fade resistant



Slip Resistance



Anti-Termites



Waterproof



Easy to Clean



Comfortable Underfoot



Scratch Resistant